

QA-ES Series II

Electrosurgery Analyzer

Technical Data



QA-ES Series II analyzes electrosurgical units quickly and accurately.

A wide load-resistance range provides 128 user-selectable loads, including very low loads for testing many of today's ESUs.

An accuracy of $\pm 2\%$ of reading down to 20 mA guarantees reliable high-frequency leakage results. With capability to run an auto-power-distribution test in as little as 1 minute, the QA-ES works fast so technicians save time.

An Ansur QA-ES software plug-in allows users to create and automatically run tests, capture data, and produce easy-to-read reports with a PC.

Key features

- Automatic power distribution measurement, including power, current, peak-to-peak voltage (closed load only), and crest factor
- Oscilloscope output
- High-frequency leakage measurements with accuracy of $\pm 2\%$ of reading
- 128 internal user-selectable test loads from 10 Ω to 5200 Ω
- Foot-switch output for triggering the ESU under test
- Ansur QA-ES software plug-in for automated test protocols
- Large display
- RS-232 and Centronic-Printer interface

Technical specifications

Generator output

Continuous operation

Continuous measurement of power, current, peak-to-peak voltage (closed load only), and crest factor

Single operation

Single measurement after the set delay time of the ESU output of power, current, peak-to-peak voltage (closed load only), and crest factor

Power distribution

Automatic measurement of power, current, peak-to-peak voltage (closed load only), and crest factor through a user-selectable load range

RF leakage current

Provides connections and load configurations to measure HF leakage from both grounded and isolated equipment

RECQM

Test the “return electrode control quality monitoring” using the QA-ES internal loads

Modes of operation

Manual or remote controlled (via Ansur)

Measurement

True-rms value of applied waveform

RMS bandwidth

30 Hz to 10 MHz (-3 dB) for instrumentation only
30 Hz to 2.5 MHz (-3 dB) with loads

Low frequency filter

100 Hz filter to avoid low-frequency disturbance or interference

Current

20 mA to 2200 mA

Current accuracy

20 mA to 2200 mA $\pm 2\%$ of reading

Load resistance

10 Ω to 2500 Ω in step of 25 Ω (@ dc)
2500 Ω to 5200 Ω in step of 100 Ω (@ dc)



Additional fixed load

200 Ω 400 W for 30 s; max 15 % duty cycle

Crest factor

The higher of the two peak voltage measurements is used for computation

Range

1.4 to 16 (V peak/V rms)

Foot-switch output

The foot switch output can be used to trigger the electrosurgical unit

Peak-to-peak voltage

0 kV to 10 kV (closed load only)
accuracy: $\pm 10\%$

Note: Measurement is taken between the active and dispersive electrodes with closed load only.

Oscilloscope output

5 V/A uncalibrated, 100 mA RF current
minimum input

Ansur QA-ES Plug-In

Remote control

All functions and tests in QA-ES may be performed from the PC

User-programmable test sequences

Allows unlimited numbers of test sequences with user-programmable templates and test limits. These tests include power distribution test, output test, HF leakage, and RECQM verification

Storage and recall

Protocol formats and data may be stored, recalled, printed out, or transferred

Temperature**Operating**

15 °C to 35 °C (59 °F to 95 °F)

Storage

0 °C to 50 °C (32 °F to 122 °F)

Display

LCD graphic display

Alphanumeric format

8 lines x 40 characters

Graphic mode

240 x 64 pixel matrix

Display control

5 F-keys, enter, cancel, control knob, and an encoder

Data input/outputs

Parallel printer port and bidirectional RS-232

Power

115/230 V ac; 48 Hz to 66 Hz, 35 VA

Housing

Metal case

Dimensions (WxDxH)

39.5 cm x 34.2 cm x 13.2 cm
(15.6 in x 13.5 in x 5.2 in)

Weight

9.8 kg (21.6 lb)

Ordering Information**Models**

2649769 QA-ES Series II 115 V Electrosurgery Analyzer (US)

2651725 QA-ES Series II 230 V Electrosurgery Analyzer (Schuko)

2770445 QA-ES Series II 230 V Electrosurgery Analyzer (UK)

2770450 QA-ES Series II 230 V Electrosurgery Analyzer (Australia)

3096390 QA-ES Series II 100 V Electrosurgery Analyzer (Japan)

Standard accessories

2716044 Manual on CD

2716032 Manual Hard Copy

2772171 ESU-Dispersive Safety Lead

2772180 ESU-CQM Safety Lead

2772209 ESU-Jumper Safety Lead

Power Cord (country specific)

2826194 Test Lead with stackable plugs

1903307 Test Lead Set with retractable sheaths

1610159 Sure-Grip Large Alligator Clip Set

Optional accessories

2461794 Carrying Case

2461802 Ansur Test Software, QA-ES Plug-in License

2461993 Data Transfer Cable, RS-232

2716059 Calibration Manual

2523266 Clamp, crocodile style, grip C, black

2523275 Clamp, crocodile style, grip C, red

About Fluke Biomedical

Fluke Biomedical is the world's leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance.

Today, biomedical personnel must meet the increasing regulatory pressures, higher quality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today's challenges.

Fluke Biomedical Regulatory Commitment

As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 certified and our products are:

- CE Certified, where required
- NIST Traceable and Calibrated
- UL, CSA, ETL Certified, where required
- NRC Compliant, where required

Fluke Biomedical.

Better products. More choices. One company.

Fluke Biomedical
6045 Cochran Road
Cleveland, OH 44139-3303 U.S.A.

Fluke Biomedical Europe
Science Park Eindhoven 5110,
5692EC Son, The Netherlands

For more information, contact us:

In the U.S.A. (800) 850-4608 or
Fax (440) 349-2307
In Europe/M-East/Africa +31 40 267 5200 or
Fax +31 40 267 5436
From other countries +1 (440) 248-9300 or
Fax +1 (440) 349-2307
Email: sales@flukebiomedical.com
Web access: www.flukebiomedical.com